

WHEEL STOPS

Creates A Barrier To Stop Vehicle Tires In Parking Spaces



- › Protects walls by preventing vehicles from going beyond a certain point
- › Durable rubber, conforms to uneven surfaces
- › Withstands harsh weather conditions
- › Embedded reflective yellow tape helps visibility at night
 - never needs painting
- › Easy to install and maintain, reinforced bolt holes
 - install in concrete, asphalt, or gravel
 - hardware sold separately



WHEEL STOPS

EPDM Rubber Wheel Stops

- ▶ Heavy duty EPDM synthetic rubber
 - made from pre and post consumer recycled rubber materials
 - highly resistant to weathering
 - years of use without cracking or deteriorating
- ▶ Embedded solid reflective stripes, made from road marking tape



PAS-PB-4

22" L, 9 lbs. 14 oz.
6 Embedded Yellow Reflectors
Pre-drilled Holes for Installation



PAS-PB-9

48" L, 21 lbs. 8 oz.
8 Embedded Yellow Reflectors
Pre-drilled Holes for Installation



PAS-PB-2L

70" L, 25 lbs.

PAS-PB-2

72" L, 31 lbs.

8 Embedded Yellow Reflectors
Pre-drilled Holes for Installation

Recycled Rubber Wheel Stop

- ▶ Durable, high quality post consumer recycled rubber
 - resistant to weathering, oil, salt, and moisture
 - won't chip, crack or crumble
 - protected from UV light
- ▶ Embedded solid reflective stripes, made from road marking tape
- ▶ Made in the U.S.A.

Made From Recycled Tires!



STN-6Y

72.5" L, 35.5 lbs.
8 Embedded Yellow Reflectors
Pre-drilled Holes for Installation



ST-4Y

48" L, 30 lbs.
4 Embedded Yellow Reflectors
Pre-drilled Holes for Installation
Special Order



STN-6W

72.5" L, 35.5 lbs.
8 Embedded White Reflectors
Pre-drilled Holes for Installation

Handicapped Parking Blue Wheel Stop



STN-6BW

72.5" L, 35.5 lbs.
8 Embedded White Reflectors
Pre-drilled Holes for Installation
Special Order

WHEEL STOPS

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	HEIGHT	REFLECTORS	WEIGHT	FASTENER HOLES	PALLET QTY
PAS-PB-4	22" Wheel Stop	22"	6"	4"	yellow, 6 ea. (3" x 4")	9 lbs. 14 oz.	2	6/Bag
PAS-PB-9	4' Wheel Stop	48"	6"	4"	yellow, 8 ea. (5" x 4")	21 lbs. 8 oz.	3	100/PL
PAS-PB-2L	6' Wheel Stop	70"	5.5"	3.625"	yellow, 8 ea. (8" x 4")	25 lbs.	4	64/PL
PAS-PB-2	6' Wheel Stop	72"	5.75"	3.75"	yellow, 8 ea. (8" x 4")	31 lbs.	4	64/PL
STN-6Y	6' Wheel Stop	72.5"	6"	4.5"	yellow, 8 ea. (7.25" x 2")	35.5 lbs.	4	60/PL
STN-6W	6' Wheel Stop	72.5"	6"	4.5"	white, 8 ea. (7.25" x 2")	35.5 lbs.	4	60/PL
STN-6BW	6' Blue Wheel Stop	72.5"	6"	4.5"	white, 8 ea. (7.25" x 2")	35.5 lbs.	4	60/PL
ST-4Y	4' Wheel Stop	48"	6"	4.5"	yellow, 4 ea. (7.25" x 2")	30 lbs.	3	72/PL

Installation Hardware Sold Separately

ITEM NO.	SIZE	DESCRIPTION	WEIGHT	INSTALLATION TYPE
PAA-SC-2S	4"	Zinc Coated Steel lag screw, washer, plug	0.27 lbs	Concrete
PAA-SC-1S	6"	Zinc Coated Steel lag screw, washer, and plug	0.22 lbs	Asphalt
PAA-SC-4B	14"	Zinc Coated Steel Spike, head 1.125", spike 0.25" dia.	0.71 lbs	Asphalt & Gravel

4" Anchor

PAA-SC-2S



6" Anchor

PAA-SC-1S



PAA-SC-4B

Note: Never use spikes or expanding anchors in concrete slabs or parking structures due to a waterproof membrane. Consult with building maintenance or engineer for correct installation procedures in these structures.

Use epoxy or construction adhesive (ie. Polyurethane PL Premium) for installations where no hardware is allowed.